

Specs. Lamp type	Voltage V	Wattage W	Average life hrs.	Mount dist. mm L ₁	Max. overall length mm L ₂	Filament	Approx. color temp. °K	Base L ₃
DDK	19	80	40	152	44.5	CC-6	3,300	GX5.3
DDL	20	150	500	194.5	44.5	CC-6	3,150	GX5.3
DDS	21	80	1,000	165	44.5	CC-6	3,125	GX5.3
DED	13.8	85	1,000	165	44.5	CC-6	3,150	GX5.3
DJT	13.8	50	1,000	152	44.5	C-6	3,150	GX5.3
EFN	12	75	50	32	42	CC-6	3,400	G6.35-1
EFP	12	100	50	32	42	CC-6	3,400	G6.35-1
EFR	15	150	50	32	42	CC-6	3,400	G6.35-1
EKN	17.5	120	120	38.1	44.5	CC-6	3,200	GX5.3
EKX	24	200	50	139.7	47	CC-6	3,400	GX5.3
ELD	21	150	40	165.1	44.5	CC-6	3,350	GX5.3
EJN				50.8	44.5		3,400	
EPV	14.5	90	500	155.2	44.5	CC-6	3,150	GX5.3
EMC	12	100	200	142	44.5	CC-6	3,100	GX5.3
DDM	19	80	50	152	44.5	CC-6	3,350	GX5.3
ELH	120	300	35	152.4	47.0	CC-8	3,350	GY5.3
ENG	120	300	15	152.4	44.5	CC-8	3,450	GY5.3
ENH	120	250	175	152.4	44.5	CC-8	3,250	GY5.3
EJM	21	150	40	38.1	47.0	CC-6	3,350	GX5.3
EKE	21	150	200	44.5	44.5	CC-6	3,250	GX5.3
EKG	19	80	25	44.5	47.0	CC-6	3,400	GX5.3
ENW/ENC	19	80	200	44.5	44.5	CC-6	3,200	GX5.3
EPK	30	80	18	44.5	44.5	CC-6	3,400	GX5.3
EPN	12	35	50	29	44.5	C-6	3,300	GX5.3
ENZ	30	50	25	29	44.5	CC-6	3,400	GX5.3
ELB	30	80	18	29	44.5	CC-6	3,400	GX5.3
EJL	24	200	50	31.8	47.0	CC-6	3,400	GX5.3
ELC	24	250	50	31.8	47.0	CC-6	3,400	GX5.3
EKZ	10.8	30	200	31.8	44.5	C-6	3,100	GX5.3
ENL	12	50	1,500	38.1	44.5	C-6	3,050	GX5.3
EPZ	13.8	50	1,000	108	44.5	CC-6	3,150	GX5.3
ENX	82	360	75	298.5	44.5	CC-8	3,300	GY5.3
ERV	36	340	75	298.5	44.5	CC-8	3,300	GX5.3
EPT	10.8	42	8,000	38.1	44.5	C-6	2,900	GX5.3
EJV	21	150	40	44.5	47.0	CC-6	3,350	GX5.3