



ランプ No	電圧 Volts	電力 Watts (電流 Amps)	バルブ形状 Bulb Type	外形寸法 mm		フィラメント形状 Filament Type	口 金 BASE	光束 Lumens	平均寿命 Life (hrs)	Vacuum-V Gas-G	Figure No.	Picture No.
				全長 M.O.L.	光中心 L.C.L.							
OP2170	6	(5)	G-35	60	9(TOP)	C-6U	BA20d/24	300	300	G		213
O-3617	100	15	G-35	56	40	C-5	E26/25	100	600	V	F	214
O-3620	100	20	G-35	56	40	C-5	E26/25	150	600	V	F	214
O-3640	100/120	30	G-35	56	40	CC-6V	E26/25	350	300	G	F	215
O-3618	110	15	G-35	56	40	C-5	E26/25	100	600	V	F	214
O-3619	120	15	G-35	56	40	C-5	E26/25	100	600	V	F	214
O-3622	120	20	G-35	56	40	C-5	E26/25	150	500	V	F	214
O-3623	220	20	G-35	56	40	C-5	E26/25	150	500	V	F	214
O-3624	240	20	G-35	56	40	C-5	E26/25	150	500	V	F	214
O-3625	100	20	G-35IF	56	40	C-5	E26/25	150	600	V	F	216
O-3630	100	25	G-35IF	56	40	C-5	E26/25	200	600	V	F	216
O-3631	110	25	G-35IF	56	40	C-5	E26/25	200	600	V	F	216
O-3627	120	20	G-35IF	56	40	C-5	E26/25	150	600	V	F	216
O-3632	220	25	G-35IF	56	40	C-5	E26/25	200	500	V	F	216
O-3633	240	25	G-35IF	56	40	C-5	E26/25	200	500	V	F	216
O-3407	12.5	(3)	G-38SPTマド	60	31.75	3C-6	BA15d/19	—	300	G		217
OP2126	6	(4.5)	G-40	67	36.5	FC-6Z	E14/26×18	360	100	G	G	218
O-3118	6	(5)	G-40	67	45	C-8	E14/26×18	260	600	G	G	219
O-3410	24	30	G-40	62	26.5	CC-8	BA21d/3	470	500	G	H	220
O-3411	24	45	G-40	62	26.5	CC-8	BA21d/3	600	500	G	H	220
M-1014	100	15	G-40Red	61	40	C-5	E26/25	50	1000	V	F	221
OP2407	10	70	G-40SPT	65	40	FC-6U	B15s/30×26	1500	100	G		222
O-3641	230	75	G-40SPT	62	25	CC-13	BA21d/3	1100	50	G	I	223
O-3412	32	(3.5)	G-50	76	31.75	CC-6	BA15d/19	2800	50	G	J	224
OP2123	6	100	G-60	86	50	C-6U	BA22d/31×30	2000	100	G		225