

Type	Voltage (V)	Wattage (W)	Lumens (L m)	Color Temp. (K)	Bulb Dia (Dmm) Max.	Length		Ave. Life (Hrs.)	Base	Fig
						(L1 mm)	(L2 mm)			
J	100~130V	100	1600	2850	9.4	114.2	117.6	1500	R7S	1
		150	2400	2900	9.4	114.2	117.6	1500	R7S	1
		200	3600	2900	9.4	114.2	117.6	1500	R7S	1
		250	4500	2950	9.4	114.2	117.6	2000	R7S	1
		300	5950	2950	9.4	114.2	117.6	2000	R7S	1
		500	11000	3000	12	114.2	117.6	2000	R7S	1
		750	15000	3000	12	185.7	189.1	2000	R7S	1
		1000	22000	3000	12	185.7	189.1	2000	R7S	1
		1000	22000	3000	12	250.7	254.1	2000	R7S	1
		1500	33000	3000	12	250.7	254.1	2000	R7S	1
	200~250V	150	2400	2900	9.4	114.2	117.6	1000	R7S	1
		200	3200	2900	9.4	114.2	117.6	1000	R7S	1
		250	3750	2900	9.4	114.2	117.6	1500	R7S	1
		300	4800	2900	9.4	114.2	117.6	2000	R7S	1
		500	9500	3000	12	114.2	117.6	2000	R7S	1
		750	16500	3000	12	185.7	189.1	2000	R7S	1
		1000	22000	3000	12	185.7	189.1	2000	R7S	1
		1500	33000	3000	12	250.7	254.1	2000	R7S	1
		2000	44000	3000	12	327.4	330.8	2000	R7S	1
		2000	44000	3000	12	—	334.4	2000	Fa4	2