



ランプ No.	電圧 Volts	電力 Watts 電流 Amps	バルブ形状 Bulb Type	外形寸法 mm		フィラメント形状 Filament Type	口 金 BASE	光束 Lumens	平均寿命 Life (hrs)	Vacuum-V Gas-G	Figure No.	Picture No.
				全長 M.O.L.	光中心 L.C.L.							
O-3011	3.5	(2.5)	T-16	44.5	28.5	C-6	BA15s/19	82	2000	G	A	247
O-3010	3.5	(2.75)	T-16	44.5	28.5	C-6	BA15s/19	138	100	G	A	247
O-3012	6.5	(2.75)	T-16	44.5	28.5	C-6	BA15s/19	314	125	G	A	247
OP2110	6	15	T-19	55	40	FC-6Z	BA15d/19	(210)	100	G	B	248
O-3112	6	15	T-19	55	38	C-6	BA15d/19	145	1000	G	B	249
OP2107B	6	15	T-19	56	38.5	FC-6Z	M16×0.75	(200)	100	G	C	250
OP2113	6	18	T-19	55	40	FC-6Z	BA15d/19	220	100	G	B	248
OP2171	6	(5)	T-19	55	28	C-6U	BA15s/19	500	50	G	A	251
OP2172	6	(5)	T-19	55	41	C-8Z	P15s	410	100	G		252
OP2107	6	15	T-19	55	38	C-8Z	M16×0.75	240	80	G	C	253
O-3430	25	(1)	T-19	55	20	CC-6	BA15s/19	700	30	G	A	254
OP2010	5	(3)	T-20	50	13.5	FC-6Z	SB22コード	120	30000	G	D	255
OP2011	5	(3.5)	T-20	50	13.5	FC-6Z	SB22コード	160	20000	G	D	255
OP2012	5	(4.5)	T-20	50	13.5	FC-6Z	SB22コード	270	20000	G	D	255
OP2173	6	12	T-20	50	28.5	FC-6Z	BA15d/19	(180)	60	G	B	256
O-3520	100	20	T-20	50	29	C-5	BA15d/19	150	600	V	B	257
O-3521	120	20	T-20	50	29	C-5	BA15d/19	150	600	V	B	257
O-3522	220	20	T-20	50	29	C-5	BA15d/19	150	600	V	B	257
O-3523	240	20	T-20	50	29	C-5	BA15d/19	150	600	V	B	257
OP2174	6	(1)	T-22	53	37	FC-12Z	BA15d/19	230	100	G	B	258
O-3115	6	(3)	T-22	53	37	C-12	BA15d/19	230	100	G	B	259
O-3524	100	20	T-22	53	30	C-5	BA15d/19	150	600	V	B	260
O-3598	120	20	T-22BF	53	30	C-5	BA15d/19	(100)	600	V	B	261
O-3502	120	20	T-221F	53	30	C-5	BA15d/19	150	600	V	B	262
O-3599	220	20	T-221F	53	30	C-5	BA15d/19	150	600	V	B	262
O-3600	240	20	T-221F	53	30	C-5	BA15d/19	150	500	V	B	262