

FSR	長さ (mm)	適合 安定器	ランプ特性			
			入力電流 (A)	入力電力 (W)	全光束 (lm)	
					W	EX-N
303T6	303	RES 361	0.10	9.5	550	610
455T6	455		0.14	14	760	840
24T6	539		0.16	16	920	1010
25T6	565		0.17	17	970	1050
606T6	606		0.18	18	1050	1150
30T6	692		0.20	20	1210	1330
32T6	743		0.21	21	1310	1440
757T6	757		0.22	22	1340	1470
36T6	844		0.24	24	1500	1650
910T6	910		0.25	25	1650	1820
42T6	999	RES 641	0.27	27	1830	2000
1060T6	1060		0.29	29	1930	2100
48T6	1149		0.32	32	2100	2300
1212T6	1212		0.33	33	2230	2450
54T6	1302		0.35	35	2400	2650
1365T6	1365		0.36	36	2500	2750
60T6	1454		0.39	39	2650	2950
1515T6	1515		0.40	40	2750	3050
64T6	1556		0.42	41	2850	3150
1667T6	1667		REN 961	0.37	37	2640
72T6	1759	0.39		39	2820	3100
1818T6	1818	0.42		41	2910	3200
96T6	2368	0.52		52	3800	4200